

WIDTH: 180 cm

WEIGHT: 590 g/m²



ENTRANCE CANOPY



RECEPTION STRUCTURE



SAIL SHADE

G U A R A N T E E S A N D L A B E L S



ADVANTAGES

- FERRARI[®] PRÉCONTRAI[®] TECHNOLOGY
- LONGER LIFESPAN
- TEAR STRENGTH
- NO DEFORMATION
- UV-RESISTANT
- SIMPLIFIED MAINTENANCE
- FIRE SAFETY FOR PUBLIC BUILDINGS
- COMPATIBLE WITH DIFFERENT GRAPHIC APPLICATIONS METHODS
- PLAIN OR STRIPED COLOURS 14 CM WIDE

COLOURS AND REFERENCES

(COLOURS GIVEN FOR INDICATION)

Precontraint 502 Plain Precontraint 542 Stripes

	Ref. 502-8102		Ref. 542-1088
	Ref. 502- 8341		Ref. 542-1270
	Ref. 502- 8861		Ref. 542-1089
	Ref. 502- 8875		Ref. 542-1091
	Ref. 502- 8116		Ref. 542-1271
	Ref. 502- 1013		Ref. 542-1272
	Ref. 502- 8151		Ref. 542-1273
	Ref. 502- 8199		Ref. 542-1274
	Ref. 502- 8204		Ref. 542-1084
	Ref. 502- 8284		Ref. 542-1086
	Ref. 502- 8256		Ref. 542-1082
	Ref. 502- 8265		Ref. 542-1083
	Ref. 502- 8296		
	Ref. 502- 8250		
	Ref. 502- 8255		
	Ref. 502- 1016		
	Ref. 502- 8053		
	Ref. 502- 8611		
	Ref. 502- 8060		
	Ref. 502- 8056		
	Ref. 502- 8552		
	Ref. 502- 8518		
	Ref. 502- 8003		
	Ref. 502- 8001		
	Ref. 502- 1125		
	Ref. 502- 8390		
	Ref. 502- 8358		
	Ref. 502- 8400		
	Ref. 502- 8115		
	Ref. 502- 8450		

TECHNICAL CHARACTERISTICS

TECHNICAL CHARACTERISTICS	PRÉCONTRAI [®] 502 AND PRÉCONTRAI [®] 542	
YARN	1100 dtex PES HT	TERUISSE
WEIGHT	590 g/sqm	EN ISO 2286-2
WIDTH	180 cm	
TENSILE STRENGTH (WARP/WEFT)	250/250 daN/5 cm	EN ISO 1421
ELONGATION UNDER LOAD	1%	200 daN/M - 23°C, 24h
TEAR STRENGTH (WARP/WEFT)	25/20 daN	DIN 53.363
ADHESION	9 daN/5 cm	EN ISO 2411
FINISH	VARNISHED BOTH SIDES	
FLAME RETARDANCY	M2/NFP 92.503 - B1/DIN 4102 - M2/UNE 23727-90 CALIFORNIA STATE FIRE MARSHAL - T 19 - NFPA 701 BS 7837 - SP FULL SCALE TEST - METHOD 2205 (502 ONLY : LP 7 - UBC 31-1) - AS 1530 - SIS 650082 - CSE 3/77 CLASS 2 - SN 198 898	
COATING THICKNESS AT THE TOP OF THE YARNS	160 µm	
EXTREME WORKING TEMPERATURES	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM	ISO 9000	

The technical characteristics shown are average values given as a guide and may be modified.

FERRARI

